

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 May 2005 (06.05.2005)

PCT

(10) International Publication Number
WO 2005/040693 A3

- (51) International Patent Classification⁷: **F24F 5/00**
F28D 5/00
- (21) International Application Number: **PCT/EP2004/011833**
- (22) International Filing Date: 18 October 2004 (18.10.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 17 October 2003 (17.10.2003) **GB 0324348**
- (71) Applicant (for all designated States except US): **OXY-CELL HOLDING BV [NL/NL]**; Kaagstraat 17-19, 8102 GZ Raalte (NL).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **REINDERS, Johannes, Antonius, Maria [NL/NL]**; Oude Warkenseweg 1, NL-7231 Warnsveld (NL).
- (74) Agent: **CLARKSON, Paul**; Howrey Simon Arnold & White, Citypoint, One Ropemaker Street, London EC2Y 9HS (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: **HEAT EXCHANGE LAMINATE**



(57) Abstract: A heat exchange laminate comprises a formable carrier layer at least partially covered with a flexible liquid retaining layer having an open structure. By forming such a laminate of two layers, desired properties such as the spatial distribution of the liquid retaining layer, can be imparted to the heat exchange laminate prior to forming. The laminate may then be conveniently formed into any desired shape by known manufacturing procedures for incorporation into a heat exchanger. The laminate may be used to cool a first fluid by evaporation of a liquid into a second fluid operating at or near its saturation point.

WO 2005/040693 A3



— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(88) Date of publication of the international search report:
16 June 2005